


Notes:

- J1** - PC-7 male
- J2** - SMA female
- J3** - DB-25 male

Connections

Conn.	Type	Pin#	Function
J1	MS1	1	+15V
J1	MS2	2	-15V
J1	MS3	3	+5V
J1	MS4	4	GND 15V
J1	MS5	5	GND
J2	MS1	1	GND
J2	MS2	2	OUTPUT
J3	MS1	1	GND
J3	MS2	2	TxD
J3	MS3	3	RxD
J3	MS4	4	RTS
J3	MS5	5	CTS
J3	MS6	6	DSR
J3	MS7	7	GND
J3	MS8	8	GND
J3	MS9	9	GND
J3	MS10	10	GND
J3	MS11	11	GND
J3	MS12	12	GND
J3	MS13	13	GND
J3	MS14	14	GND
J3	MS15	15	GND
J3	MS16	16	GND
J3	MS17	17	GND
J3	MS18	18	GND
J3	MS19	19	GND
J3	MS20	20	DTR
J3	MS21	21	GND
J3	MS22	22	GND
J3	MS23	23	GND
J3	MS24	24	GND
J3	MS25	25	GND



ELVA-1

46 Robezu str. LV-1004 Riga • Latvia
 Phone : +371-7-065100
 Fax : +371-7-065102
 In St. Petersburg, Russia
 Fax : +7-812-325-5856, Att. D. Korneev
 E-mail : korneev@exch.nnz.spb.su
 INTERNET: <http://www.elva-1.spb.ru/>

TITLE

**Digital Driver for VCVA series
 Voltage Controlled Attenuator.
 Part No. DVC-RS-485/12**

DATE

12.09.00

SHEET

1 OF 1

SPEC. NO.

45DC02612